



CAUDWELL MARINE™ AXIS DRIVE™ GASOLINE RANGE

SPECIFICATIONS AND STANDARDS:	250 VI	300 VI	350 VI
ENGINE TYPE	V6	V6	V8
HORSEPOWER	250	300	350
DISPLACEMENT	3500 CC	3500 CC	4500 CC
RPM RANGE	5500-6000	6000-6700	6200-6900
CYLINDERS	6	6	8
ALTERNATOR OUTPUT @ WOT	120 AMPS	120 AMPS	120 AMPS
COMPRESSION RATIO	10.3	10.3	10.5
FUEL / INDUCTION SYSTEM	MPI	MPI	MPI
DIGITAL THROTTLE & SHIFT	STANDARD	STANDARD	STANDARD
SOFT ENGAGE ELECTRO -HYDRAULIC CLUTCH	STANDARD	STANDARD	STANDARD
CLOSED COOLING	STANDARD	STANDARD	STANDARD
WATER DRAIN SYSTEM	STANDARD	STANDARD	STANDARD
ENGINE LUBRICATION	MODIFIED WET SUMP	MODIFIED WET SUMP	MODIFIED WET SUMP
POWER-TRAIN LUBRICATION	DRY SUMP, DIPSTICK CHECK AND FILL	DRY SUMP, DIPSTICK CHECK AND FILL	DRY SUMP, DIPSTICK CHECK AND FILL
IGNITION SYSTEM	ELECTRONIC	ELECTRONIC	ELECTRONIC
STARTING SYSTEM	TOUCH & RELEASE	TOUCH & RELEASE	TOUCH & RELEASE
GEAR RATIOS	2.68 - 1.88	2.68 - 1.88	2.68 - 1.88
C.A.R.B RATING *	3 STAR	3 STAR	3 STAR
WEIGHT (DRY)	360 KG	360 KG	375 KG
TRIM SYNCHRONIZATION	STANDARD	STANDARD	STANDARD
RPM SYNCHRONIZATION	STANDARD	STANDARD	STANDARD
RPM HOLD / SPEED CONTROL	STANDARD	STANDARD	STANDARD
EXTERNAL TILT SWITCH	STANDARD	STANDARD	STANDARD
DUAL RATE POWER TRIM AND TILT	STANDARD	STANDARD	STANDARD
THERMOSTATIC COOLING SYSTEM	STANDARD	STANDARD	STANDARD
5 YEAR CORROSION WARRANTY	STANDARD	STANDARD	STANDARD
3 YEAR LIMITED PARTS AND LABOUR WARRANTY	STANDARD	STANDARD	STANDARD

* UNDER EVALUATION



Caudwell Marine (Pty) Ltd
Thunder City Complex
Tower Road
Cape Town International Airport
South Africa 7525

Tel: +27 (0)21 934 8007
Fax: +27 (0)21 934 8003

email: info@caudwellmarine.com
web: www.caudwellmarine.com